

## ATF POWER LV Red

### Automatic transmission fluid

**ATF POWER LV Red** is a synthetic high quality versatile automatic transmission fluid intended for 6-speed, 8-speed and 9-speed automatic car transmissions. Subjected to extreme testing.

**ATF POWER LV Red** guarantees maximum performance of the automatic transmission. At the same time, the wear of heavily loaded components is minimized due to the specifically matched oils.

**ATF POWER LV Red** is based on a synthetic base in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- Excellent lubrication, even under extreme conditions.
- Very high protection against wear, corrosion and foam.
- High "shear stable".
- Very low Pour point, can be used by very cold temperatures.
- High Viscosity Index.

**ATF POWER LV Red** meets the performance criteria where the following specifications are asked:

Aisin-Warner JWS 3309

Aisin-Warner JWS 3324

Aisin-Warner AW-1/AW-2

**Audi**

**BMW**

**VW**

**Opel**

5 HP LT71 141

LT71 141

G 050 162

88863400/88863401

G 052 025 A2

ATF 2/3+/6/7

G 055 005

VI

**KIA**

**Ford**

**Toyota**

**Volvo**

ATF SP-II/-III/-IV

MERCON

ATF T-III/-IV

97325

ATF SP-IVM

WSS M2C 922A1

ATF D-II/-III

PN 31256774

**Nissan**

**GM**

**RENAULT**

**MAZDA**

Matic Fluid -

DEXRON III-H

Matic D2

ATF FZ

C/D/J/K/P/S/W

TASA

Samsung SATF-D

ATF A7

For a more detailed list, see the following pages.

### Typical Analysis

| Properties                   | Unit               | Method          | Typical Value |
|------------------------------|--------------------|-----------------|---------------|
| Color                        |                    | visual          | Red           |
| Density @15 °C               | kg/m <sup>3</sup>  | ASTM 4052       | 846.4         |
| Kinematic Viscosity @ 40 °C  | mm <sup>2</sup> /s | ASTM D7042      | 30.0          |
| Kinematic Viscosity @ 100 °C | mm <sup>2</sup> /s | ASTM D7042      | 6.0           |
| Viscosity Index              |                    | ASTM D2270      | 154           |
| Flash Point COC              | °C                 | ASTM D92        | >201          |
| Pour Point                   | °C                 | ASTM D7346      | -47           |
| Date Issued: 4-9-2025        | Supersedes: -      | Revision Nr.: 0 |               |



ATF LV Red is suitable for use where the following specifications are required:

Acura ATF-Z1  
Aisin Warner JWS 3309, JWS 3314, JWS 3324, AW-1, AW-2  
Allison C-3, C-4, TES-389  
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)  
Audi/VW G 052 025 A2, G 052 055, G 052 990, G 052 162 A1/A2, G 053 025 A2  
Audi/VW G 055 005 A/A1/A2/A6, G 055 025 A2, G 055 162 A2/A6, G 055 540 A2, G 060 162  
Bentley PY112995PA  
BMW LA2634, LT71141, ZF 5HP18FL/5HP24/5HP30, 7045E, ETL 8072B, ATF 2/3+/6/7  
BMW 83 22 2 152 426, 83 22 2 305 397, 83 22 2 289 720  
Bosch TE-ML 09  
CAT TO-2  
Chrysler ATF+/-2/+3, MS7176E  
Chrysler/Dodge MOPAR AS 68 RC, AS 69 RC  
Chrysler/Dodge/Jeep 05127382AA, 68043742AA, 68157995AA, 68157995AB, 68049954AA  
Chrysler/Dodge/Jeep 68218925AA, 68218925AB  
Chrysler/Dodge/Jeep MOPAR SP IV, 68171866AA/68171869AA  
Daewoo LT 71141  
Daihatsu AMMIX ATF D-II, AMMIX ATF D-III SP  
FIAT T-IV type, 9.55550-AV5, 9.55550-AV6  
Ford MERCON®, MERCON® LV, ATF C-ML5, FNR5  
Ford 138CJ, 166H, 922A1, 924A  
Ford/Lincoln/Mercury XT-6-QSP or -DSP, XT-2-QDX, XT-2-QSM, XL-12  
Fuso ATF-II, ATF-SPIII, ATF-A4  
GM TASA, DEXRON®-II/IIID/IIIE/IIIG/IIIH/VI, AutoTrak II  
GM 1940700, 1940767, 21005966, 22717466, 88900925, 9986195, 93160393  
GM/GMC/Opel/Saturn AW1, Saturn VI, 88863400, 88863401  
Hino Blue ribbon ATF  
Honda ATF-Z1, ATF Ultra II, DW-1, Type 3.0, Type 3.1  
Hyundai/Kia SP-IV, SP-IV M, SPH-IV, SP-IV-RR, SP-III, Dex-II/ SP-II, NWS 9638, 040000C90SG  
ISUZU ATF WSI  
ISUZU BESCO ATF-II, ATF-III, ATF SP, SCS Fluid, 08200-9001  
Jaguar ATF 3403 M115, ATF 3403-M115, ATF LT71141, ZF 5HP24, JLM20238, JLM 20292, K17, 8432  
Jaguar 02JDE26444  
JASO M315-2013 1A, 1A-LV, 2A  
JEEP ATF+3  
KIA ATF SP-II, SP-III, SP-IV, SP-IVM  
Land Rover TYK500050, LR0022460, LR023288  
Lexus JWS 3309  
M 1375.4  
MAN 339A  
Maserati 231603  
Mazda ATF D-II, M-III, M-V, FZ, A7, F-1, S-1, N-1, 3317  
MB ZF 4HP20  
MB 236.3, 236.5, 236.6, 236.7, 236.8, 236.9, 236.11, 236.12, 236.14, 236.15, 236.17  
MINI COOPER T-IV  
Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, ATF-MA1, ATF PA  
Nissan Matic Fluid C, D, J, K, P, S, W  
Opel/GM 19 40 700, 19 40 767, 21005966, 22 17466, 88900925, 9986195  
Peugeot ZF 4HP20, Peugeot Citroen Z 000169756, (PSA) AL4 Automatic gearbox oil (#9730.AE)  
Porsche ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV, 000 043 205 09, 000 043 205 28  
Porsche 999 917 547 00, Z 000169756  
PSA B71 2340, Z 000169756  
Renault DPO/AL4, Matic D2  
Renault Samsung SATF-D  
Saab T-IV, 93 165 147, 93 160 393  
Saab Power Steering Fluid 2634, 45 30 09 800, 93160548  
Ssang yong DSIH 5M-66  
Subaru ATF, ATF 5AT, ATF HP, K0140Y0700  
Suzuki AT OIL 5D06, ATF 2326, ATF 2384K, ATF 3314, ATF 3317  
Toyota ATF D-II, ATF D-III, ATF T-III, ATF T-IV, ATF WS  
Vickers M2950-S, I-286-S  
Voith 55.6335.xx (G607)  
Volvo 97325, 97335, CE 97340, CE 97341, CE 97342, PN 1161521, PN 1161540/1161640, PN 31256774/31256675  
Volvo PN 161621  
ZF 3, 4, 6, 8 & 9 speed transmission  
ZF TE-ML 05L, 09, 11A, 11B, 21L

